# SB60x32-8TD-xH-SC

60 X 32 SOLID SURFACE SHOWER BASE WITH RH OR LH TRENCH DRAIN IMI SOLIDCAST™

Exterior Dimensions:  $593/4 \text{ W} \times 313/4 \text{ D}$ Note: Base dimensions may vary +/-  $\frac{1}{4}$ "



### Material to be stacked on pallets.

#### COLOR & TRIM OPTIONS

Standard Color	Code
White	SW

Additional custom colors available.

### **FEATURES**

- Single-piece cast engineered stone receptors
- Non-porous through body color material (no gel-coat or other top-coat finishes included)
- Contains a minimum of 60% natural stone material
- Contains premium grade solid surface resin, NPG-isophthalic (ISO), UV inhibited acrylic based polyester resin
- Meets Slip-Resistance Requirements as described in ANSI Code 2514.03.A
- Features a water-tight tile flange anywhere where the wall meets the base that is not thicker than 3/16"
- Pre-leveled, rests on subfloor

### **STANDARDS AND RATINGS**

- Typical CSI Code: 22 42 23 (Div 22)
- ANSI
- ASTM (Fire Rating)
- MAS Certified Green
- Slip-resistance: SCoF = 0.6+, wet; DCoF = 0.42+
- Breaking strength: 250 lbs. minimum

\*See terms and conditions for details.







inches

imitoday.com

## 60 X 32 SOLID SURFACE SHOWER BASE WITH RH OR LH TRENCH DRAIN IMI SOLIDCAST™

Note: Base dimensions may vary +/- 1/4"

**TECHNICAL SPECIFICATIONS** 



FEATURES Dimensional Tolerance ± 1/4". Dimensions needed for site preparation should be measured from the unit. American Bath Group assumes no responsibility for preparatory work.

**→** 4 1/2"

Type and Model #	Material	Shower Base	Pieces
Shower Base #SB60x32-8TD-xH-SC	Cast Solid Surface	Anti-Slip/Textured Finish	1

### DIMENSIONS

Solid Surface Solutions

Specifications	inches
Shower Base Depth:	31 3⁄4
Shower Base Width:	59 <b>¾</b>
Curb Height:	2 3⁄4
Curb Width:	3

### SUGGESTED DRAINS

#### Image Description



Solvent Weld type fitting similar to Oatey Part No. 42097



Compression type "No-Caulk" fitting similar to Oatey Part No. 42099

Rev. 12.12.22